



CIRCULAR CONCRETE PIPE



| SIZE | END AREA SQ. FT. | WALL THICKNESS | WEIGHT (lbs/ft) |
|------|------------------|----------------|-----------------|
| 12" | .785 | 2¾" | 139 |
| 15" | 1.227 | 3" | 187 |
| 18" | 1.767 | 2½" | 186 |
| 21" | 2.405 | 2¾" | 218 |
| 24" | 3.142 | 3" | 264 |
| 27" | 3.976 | 3¼" | 322 |
| 30" | 4.909 | 3½" | 384 |
| 33" | 5.940 | 3¾" | 451 |
| 36" | 7.069 | 4" | 524 |
| 42" | 9.621 | 4½" | 686 |
| 48" | 12.566 | 5" | 867 |
| 54" | 15.904 | 5½" | 1,068 |
| 60" | 19.635 | 6" | 1,295 |
| 66" | 23.758 | 6½" | 1,542 |
| 72" | 28.274 | 7" | 1,811 |
| 78" | 33.183 | 7½" | 2,098 |
| 84" | 38.485 | 8" | 2,410 |
| 90" | 44.170 | 8½" | 3,020 |
| 96" | 50.266 | 9¾" | 3,355 |

CIRCULAR CONCRETE PIPE IS MADE TO SPECIFICATIONS C-76, C-361, C-443 AND C-655.

WEIGHTS MAY VARY SLIGHTLY ACCORDING TO THE REQUIREMENTS OF THE JOINT DESIGN, WHICH MAY ADD THE WEIGHT OF A BELL OR MODIFIED BELL.